

KTR COUPLINGS

1. ROTEX COUPLING : Flexible Jaw Couplings



Bore = 6mm- 200mm & Torque up to 28000 NM

2. BOWEX : Curved Tooth Gear Coupling



Bore = 6mm – 125mm & Torque up to 5000 NM

3. ROTEX -GS : Backlash Free Servo Couplings



Bore = 5mm – 90mm & Torque up to 3600 NM

4. TOOLFLEX : Metal bellow-type coupling



Bore = 3mm – 65mm & Torque up to 600 NM

5. REVOLEX-KX & KXD : Flexible Pin & Bush Coupling



Bore up to 650mm & Torque up to 1220000 NM

6. POLYNORM : Flexible Coupling



Bore = 40mm – 280mm & Torque up to 67000 NM

7. RADEX –N : Steel Lamina Couplings



Bore = 20mm – 330mm & Torque up to 280000NM

8. RIGIFLEX-N : Steel Lamina Coupling



Bore = 50mm – 400mm & Torque up to 280000 NM

9. FLANGE COUPLING type FLE-PA



Bore = 20mm-125mm & Torque up to 4250 NM

10. GEARex (All Steel Gear Coupling)



Bore = 50mm-276mm & Torque up to 135000 NM

KTR COUPLINGS

CLAMPING SETS & PRECISION JOINTS



External Clamping Sets



Internal Clamping Sets



PRECISION JOINTS

TORQUE LIMITERS:



RUFLEX – Torque Limiter



Backlash Free Overload System

HYDRAULIC COMPONENTS



Bell Housing & Accessories



Tanks & Accessories



Damping Rods